

digital imaging

- printing
- copying
- faxing
- scanning
- networking

digital office solutions

PAGESTATION GP225



**Document Handling**

**Print/Copy Speed:** 22 ppm

**Paper Capacity:** 3,050 sheets (max)



**Standard supply:** 1,050 sheets

**Cassettes**

Standard: Dual Cassettes (500 sheets each),

Tray 1: A4-A5, Tray 2: A3-A5, 64-80gsm

**Bypass:** 50 sheets, A3-A6R, 64-128gsm

**Output Paper Size/Weight:**

A3-A6R, 64-128gsm



**Double siding:** A3-A5,

64-80 gsm, 1 to 100 copy select



**Document Finishing:**

Sort/Group/Staple-Sort,

Transparency Interleaving



**Warm Up Time:** 8.6 seconds

**First Copy Out Time:** 9.2 seconds

**Auto Paper Selection:** Yes

**Sleep Mode:** Yes

**Image Handling**

**Image Manipulation:**

Multi-Up (up to 4 in 1),

Zoom - Preset Ratios & Scaling,

Mirror Imaging, Negative/Positive

**Area Designation for Framing & Blanking:** Yes



**Network Management**

**Network Topology:**

Ethernet, Token Ring (optional)



**Network Protocols:** TCP/IP,

Novell IPX 802.2 & 802.3,

SMB For Windows,

AppleTalk over Ethernet



**Operating Systems:**

Novell Netware 3.X, Novell

Netware 4.X, Windows '95/'98, Windows NT,

Apple Macintosh and several

UNIX systems

**Drivers:** Windows '95/'98,

Windows NT 4.0,

Apple Macintosh 7.x, OS



**Connecting Ports:** 10/100BaseT,

AUI & Parallel as Standard,

10 Base2/BNC

with Optional Transceiver,

& Token Ring with Optional Card



**Network Utility Software:**

Netspot Software,

Fiery Webtools, Fiery Downloader



**Printer Specific Features**

**Image Quality:**

2400 x 600 dpi Resolution,

256 Greyscales



Adobe PostScript® 3\*

PCL: 5e

**Memory Size:**

Std = 32MB, Max = 64MB



**Hard Drive:** 3.2GB - For Spooling,

Re-Printing and Font Storage



**Fax Specific Features**

**Transmission speed:** 6 seconds\*

(ECM-MMR mode)

**Modem speed:** 14,400 max bps\*

**Double siding:**

Transmission And Reception



**Memory Size:**

Std. = 1MB/52 pages\*\*

(3MB/9MB Upgrade Options)



**PC-Fax:**

See Network Management (PDL same as Printer)

**Walk-Up Fax Only:**

One Touch Destinations: 60

Coded Speed Dial Destinations: 140

Confidential Mailboxes: 100

Memory Lock: Yes

Document Sent Stamp: Yes

Multiple Print, Relay Broadcast: Yes

Scanning Speed: 1.58 seconds

**Copier Specific Features**

**Copy Select:** 1 to 100

**Mixed Original Copying:** Yes

**Touch Screen Display:** Yes

**Image Manipulation:**

Manual Zoom: 25 - 800%,

Image Editing



**Image Quality:**

1200 x 600 dpi Resolution,

256 Greyscales



**Job Recall:** Last 3 jobs

**Nameable Job Memories:** 5

**ID Settings:** 100 Codes

**Scanning Specific Features**

**Scanning size:** A3-A6



**Memory size:** 5MB Std, 10MB Max

**Image Quality:** 40-2400 dpi equivalent

**Scanning Modes:** Black/White (1 Bit) 16 Grey

Scales (4 Bit) 256 Grey Scales (8 Bit)

**Drivers:** TWAIN/ISIS



**Network Scanning:** To E-mail, File, or Web Browser

**Dimensions:** W585 mm x D700 mm x H571 mm

**Options...**

Recirculating Document Feeder (RDFG1)

Cabinet (GP225CABSPAN)

4 Cassette Pedestal (GP225CASSPED)

Output Tray (GPMULTRAYB2 / GPMULTRAYB3)

10 Bin Staple Sorter (GP225STASORT)

Projector (GP225PROJECT)

Image Creation Board (GP225IMCREAT)

Canon X2e Printer Controller

(GP225PS/PCL)

Scanning Kit (GP225SCANNER)

5MB Scanning Memory Upgrade (GP225SCANMB)

AXIS 7000 Network Scan Server (AXISNETSCAN)

\* Sending a standard document (Canon Fax Standard Chart No.1) to a Canon fax, excluding control times and without telephone interference.

\*\* Canon Fax Standard Chart No. 1.

Specifications subject to change without notice.

Adobe and PostScript are trademarks of Adobe Systems incorporated which may be registered in certain jurisdictions. All other trademarks acknowledged.

